AAP Catalogue Edition 2025

Published March 2025













Security & Automation

Security & Control



Gate Automation





Intercom Solutions





CCTV Solutions





Contents Page

EliteAlarm Kit's	5
EliteAlarm EC Kit's	6
EliteAlarm EC PLAS	8
EliteAlarm EC System	9
EC Alarm Keypads	12
EC Alarm Panel Accessories	13
Piezos, Strobes & Sirens	18
Indoor & Outdoor Detection Devices	20
Wireless Detectors	26
Reed Switches	27
Pendants & Transmitters	29
Elsema Wireless Range	30
Monitoring & Cellular	33
Access Control	35
Mag Locks, Strikes & Door Holders	39
Intercom Solutions	43
Gate Automation with Beninca	49
Fire Accessories	56
Batteries	58
Security & CCTV Cable	61
Control Relays & Timers	63
Plastic Enclosures	64
Plugpacks	65
Power Supplies	66
Drill Bits	68
CCTV Solutions	72





Security & Automation

Arrowhead Alarm Products was established in 1986 with a philosophy to provide top quality security equipment with an emphasis on expert back up & support. The EC security & control system is designed and manufactured in our purpose built facility in Highgate Industrial Park located in Silverdale, Auckland.

On site we have a specialised team of software and hardware engineers complimented by our lead free high speed pick & place manufacturing plant and multi stage quality control system. Each and every product we manufacture is also tested in house. This start to finish process makes us so confident that we put a 5 year warranty on everything we build. Our exclusive online technical support library and factory trained engineers provide unprecedented support for our loyal technicians.

Smartphone App & Monitoring

Intelligent Access, Control & Monitoring At Your Fingertips

Move your security to the cloud & stay in touch with your home or business. Our EliteCloud smartphone app & management dashboard puts you in control, anytime & from almost anywhere. Now offering the ability to view your TVT cameras all through the EliteCloud App. Note: Subject to device compatibility.





EliteControl Kit's



Brought to you by









	EC-KIT LCD	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-LCD & 4C2-100-CU Also available with a black external siren - EC-KIT LCD BLACK
	EC-KIT LCD NC	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-LCD. Note: excludes 4C2-100-CU <i>Also available with a black external siren - EC-KIT LCD NC BLACK</i>
,	EC-KIT TOUCH W	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-TOUCH W & 4C2-100-CU Also available with a black external siren - EC-KIT TOUCH W BLACK
	EC-KIT TOUCH W NC	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-TOUCH W. Note: excludes 4C2-100-CU <i>Also available with a black external siren - EC-KIT TOUCH W NC BLACK</i>
	EC-KIT TOUCH B	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-TOUCH B & 4C2-100-CU Also available with a black external siren - EC-KIT TOUCH B BLACK

Alarm Kits



EC-KIT KP W	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-KP W & 4C2-100-CU Also available with a black external siren - EC-KIT KP W BLACK
EC-KIT KP W NC	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-KP W. Note: excludes 4C2-100-CU <i>Also available with a black external siren - EC-KIT KP W NC BLACK</i>
EC-KIT KP B	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-KP B & 4C2-100-CU Also available with a black external siren - EC-KIT KP B BLACK
EC-KIT KP B NC	Complete EC alarm kit. Includes EC-PCB, plastic cabinet & transformer, 2 x OPT-FLX-S-ST, DM12-7.5, EC-SIREN, PS209-R, EC-KP B. Note: excludes 4C2-100-CU

Also available with a black external siren - EC-KIT KP B NC BLACK

Control your alarm with EliteCloud

Features

- System history
- Live sensor status
- View TVT cameras
- Control up to 32 outputs
- Up to 10 sites per app user
- Up to 100 app users per site
- Customisable favourites buttons
- Customisable push notifications
- Ongoing feature enhancement

Sensors Controls 9 Carpark PIR 54


EC-IoT

Plug on Ethernet board for EC-PCB



5 Year Warranty

For full history of your EliteControl system, consider adding the EliteCloud app as this will provide you with the most detailed and up to date information of your security system. Note: EC-PCB requires EC-IoT for app connectivity.







EC-PLAS	EC-PCB alarm panel in plastic cabinet & transformer. Note: excludes keypad
EC-PLAS LCD	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-LCD keypad
EC-PLAS LCD PROX	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-LCD PROX keypad
EC-PLAS TOUCH W	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-TOUCH W keypad
EC-PLAS TOUCH B	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-TOUCH B keypad
EC-PLAS KP W	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-KP W keypad
EC-PLAS KP B	EC-PCB alarm panel in plastic cabinet & transformer, includes EC-KP B keypad

Alarm Panels





EC-PCB	Infinity Series Control Panel with integrated access control, options for long range wireless & more. For app connectivity you will require EC-IoT (sold separately)
EC-i PLC/U	Infinity Series Panel mounted in EC-CAB-1A with integrated access control, options for long range wireless & more. For app connectivity you will require EC-IoT (sold separately)
EC-KP W	EliteControl capacitive interface for EC security systems (white). Dimensions W74 x H118 x D12mm
EC-KP B	EliteControl capacitive interface for EC security systems (black). Dimensions W74 x H118 x D12mm
EC-TOUCH W	5" Touch Keypad with white surround, compatible with EC, ESL- 2, ESX, ESL. Dimensions W143 x H103 x D15mm <i>Also available with prox reader - EC-TOUCH W PROX</i>
EC-TOUCH B	5" Touch Keypad with charcoal surround, compatible with EC, ESL-2, ESX, ESL. Dimensions W143 x H103 x D15mm <i>Also available with prox reader - EC-TOUCH B PROX</i>
EC-LCD	Full English text LCD keypad for EC series control panel. Multi function with assignable buttons



EC System

EC-LCD PROX	Full English text LCD keypad for EC control panel series. Multi function with assignable buttons & built in proximity reader for access control
EC-i DIALLER	Plug on dialler board for EC-PCB with built in DTMF decoder & supports canned voice messages. Also supports 3rd party devices
EC-i 4G	Plug on 4G cellular board for EC-PCB & EC-i security and control panel
EC-IoT	EC-IoT EliteCloud app & monitoring module for EC security systems. Note: EliteCloud App sold separately
EC-i RS232	RS232 plug on module for the EC control panel. Allows 2-way communication between the EC & automation system
PROX READER USB	125K proximity reader for simple prox card entry into the EC system. Simple scan to panel technology
EC-SCC BATT	Battery holder for EC series and used in conjunction with EC-CAB MET (suitable for DM12-5, 7 & 9A batteries)
EC-SCC PLATE	Adapter mounting plate for EC series and used in conjunction with EC-CAB MET series (requires EC-SCC PLATE)
EC-SCC PSU	24V DC 2.2A power module with IEC. Suitable for EC series cabinet and system

EC System



	EC-SCC PSU5	13.8V 5A (battery backup) IEC Power Cable, for Structured Cabling Cabinet, Smart Compatible with: EC-A2, EC-O4 & EC-Z8
	EC-A2 REX	2 Door Access Control Module for EC & EC-i systems only
	EC-04	4 relay output expander for EC security & control system
	EC-Z8	8 zone expander module for EC security & control system
I account	PW WIEGAND	Outdoor prox/PIN reader. IP66 outdoor ready, 40 bit wiegand with backlit keys. Used in conjunction with EC- A2
	PW WIEGAND-NK	Outdoor prox reader. IP66 outdoor ready, 40 bit wiegand with backlit keys. Used in conjunction with EC-A2
1 20000 1 20000 1 20000 1	PW WIEGAND-SK1	Outdoor prox/PIN reader. IP66 outdoor ready, 40 bit wiegand with backlit keys. Used in conjunction with EC- A2
1	PW WIEGAND-SK4	Outdoor prox/PIN reader. IP66 outdoor ready, 40 bit wiegand with backlit keys. Used in conjunction with EC- A2
	SCC-28	28" structured cabling cabinet (flush mount). Dimensions 725 x 355 x 90mm. Can be used with EC- SCC plates & expander modules



EC System



EC-KP W	EliteControl capacitive interface for EC security systems (white). Dimensions W74 x H118 x D12mm
EC-KP B	EliteControl capacitive interface for EC security systems (black). Dimensions W74 x H118 x D12mm
EC-TOUCH W	5" Touch Keypad with white surround, compatible with EC, ESL- 2, ESX, ESL. Dimensions W143 x H103 x D15mm
EC-TOUCH B	5" Touch Keypad with charcoal surround, compatible with EC, ESL-2, ESX, ESL. Dimensions W143 x H103 x D15mm
EC-TOUCH W PROX	5" Touch Keypad with white surround, includes built-in prox. Compatible with EC, ESL-2, ESX, ESL. Dimensions W143 x H103 x D15mm. 2 x PROX EM4100 included
EC-TOUCH B PROX	5" Touch Keypad with charcoal surround, includes built-in prox. Compatible with EC, ESL-2, ESX, ESL. Dimensions W143 x H103 x D15mm. 2 x PROX EM4100 included
EC-LCD	Full English text LCD keypad for EC series control panel. Multi function with assignable buttons
EC-LCD PROX	Full English text LCD keypad for EC control panel series. Multi function with assignable buttons & built in proximity reader for access control

Alarm Keypads





EC-PCB	Infinity Series Control Panel with integrated access control, options for long range wireless & more. For app connectivity you will require EC-IoT (sold separately)
EC-IoT	EC-IoT EliteCloud app & monitoring module for EC security systems. Note: EliteCloud App sold separately
EC-i DIALLER	Plug on dialler board for EC-PCB with built in DTMF decoder & supports canned voice messages. Also supports 3rd party devices
INFINITY LINK	Wireless transceiver 916Hz for EC control panel & this board will allow the infinity wireless products to control & be controlled by the panel
INFINITY REMOTE	Wireless remote kit with 2 x Infinity Remotes and 1 x Infinity Link 916Mhz Transceiver

INFINITY REMOTE

00

Wireless 4 button remote with haptic feedback 916Mhz

Arrowhead Alarm Products

EC control panel (note: requires INFINITY LINK)

Page 13

Alarm Accessories

T	INFINITY MOTION	Wireless PIR motion sensor 916Mhz for EC control panel (note: requires INFINITY LINK)
	INFINITY INPUT	Wireless magnetic door/window contact with input 916Mhz for EC control panel (note: requires INFINITY LINK)
	INFINITY MOTION IP54	Wireless outdoor dual tech motion sensor 916MHz for EC control panel (note: requires INFINITY LINK)
	INFINITY SIREN	Wireless outdoor siren/strobe 916Mhz for EC control panel (note: requires INFINITY LINK)
0	INFINITY PANIC	Wireless waterproof panic single button 916Mhz for EC control panel (note: requires INFINITY LINK)
	INFINITY OUTPUT	Wireless I channel output 916Mhz for EC control panel (note: requires INFINITY LINK for EC integration but can also be standalone)
	INFINITY TX-1	Wireless waterproof single button 916Mhz with haptic feedback for EC control panel (note: requires INFINITY LINK)
	INFINITY TX-B	Wireless single channel transmitter in box 916Mhz (note: compatible with EC control panel and INFINITY OUTPUT)
	EC-A2 REX	2 Door Access Control Module for EC & EC-i systems only
	EC-Z8	8 zone expander module for EC system. Includes 2 x quick connect keypad bus sockets

Page 14

	EC-04	4 relay output expander module for EC system. Includes 2 x quick connect keypad bus sockets
0	USB A-LINK	Upload download link for the ESL-2 system & IP-Module
A long the s	EC-TAMPER P	Plastic cabinet tamper, compatible with EC-CAB & EC-CAB- 1A
	EC-CAB	Plastic cabinet for EC system. Holds 12V 7.5A battery, supports 1.4A power supply & multiple board locations with clip in tabs. Dimensions L323 x W293 x D87mm
	EC-CAB 1A	Plastic cabinet for EC system. Holds 12V 7.5A battery & multiple board locations. Includes 1.4A power supply with clip in tabs. Dimensions L323 x W293 x D87mm
W. Martin	ESL-2 IoT	EliteControl Plug on APP/IP-MODULE for ESL-2 System (hardware only - app sold separately)
W. Arth	ESL-2 DIAL POD	EliteControl Plug on dialler for ESL-2 System
	RM-0001A	EliteControl 4 button remote (with sliding cover) 433Mhz
	RM-8006A	EliteControl 4 button remote (with sliding cover) 303Mhz
	RM-8006B	EliteControl 4 button remote (with sliding cover) 915Mhz

ELITE TRANS-KIT M	1.4A transformer 17VAC compatible with EC-CAB MET series. Includes terminal block & screws
ELITE TRANS	1.4A transformer 17VAC compatible with EC-CAB and comes standard with all EC KIT's
ELITE TRANS-KIT	1.4A transformer 17VAC with plastic fuse terminal block & screws. Compatible with EC PLAS & EC-CAB
EC-PSU2	13.8V 1.4A Plug on power supply for EC-A2, O4 & Z8 (battery backup)
EC-TAMPER M	Tamper for EC Metal Cabinet Flush and Surface versions (EC-CAB MET F & EC-CAB MET S)
STANDOFF 3mm	Pack of 10 stick on standoffs for PCB with 3mm holes
STANDOFF 4mm	Pack of 10 stick on standoffs for PCB with 4mm holes
EC-CAB MET S	EC Surface Metal Cabinet Only (no transformer). Dimensions (lid) 388mm x 283mm x D99mm
EC-CAB MET F	EC Flush Metal Cabinet Only (no transformer). Dimensions (lid) 410mm x 307mm x D99mm
SCC-28	28'' structured cabling cabinet (flush mount). Dimensions 725 x 355 x 90mm Can be used with EC-SCC plates & expander modules

•	EC-MET LOCK	Lock & Key for the EC-CAB MET (includes 2 x keys)
	EC-SCC BATT	Battery Holder for EC range and used in conjunction with EC-CAB MET series (for 5, 7 & 9A batteries)
	EC-SCC PLATE	Structured cabling cabinet mounting plate for EC product range
	EC-SCC PSU	24VDC 2.2A Power Module with IEC for Structured Cabling Cabinet
	WIEGAND-MINI	Mini Wiegand interface for ESL-2 & ESX systems
	BEANIE GEL	Gel Filled Crimp Connector (Pack 100 pcs)
WARNING Warning Warner Warner Warner Warner Warner	WARNING STICKER- BLACK	EliteControl Outdoor Warning Label 'These premises are protected by an EliteControl security system'. Dimensions: 152x72mm
WARNING THESE PREMISES ARE PROTECTED YAN ELECTRONIC INTRUDER ALARM SYSTEM	WARNING STICKER	Red & white outdoor security warning sticker. Dimensions L158mm x W79mm
Rep	WiFi KIT	Pre programmed pair of wifi modules (1 x master & 1 x slave). Simply plug the master into your router & the slave into the module, connect the power for secure wireless path
Land Land Land Land Land Land Land Land	WIFI LR-CPE-300P- KIT	Long range outdoor wireless bridge with maximum transmission range of 1km.Supports POE solutions and plugpack included
And the second s		transmission range of 1km.Supports POE solutions and






0

EK105

Top hat piezo surface mount (114dB & 120mA @12VDC). Dimensions dia. 86mm x D42mm

EK105-2T	Combo top hat piezo & chime with adjustable volume chime output (114dB & 230mA @ 12VDC). Dimensions dia. 86mm x D42mm
PS209	Surface mount internal piezo (114dB & 150mA @ 12VDC. Dimensions dia. 54mm x D47mm



10	PS209-R2T	Combo flush mount piezo & chime with adjustable volume chime output (114dB & 230mA @ 12VDC). Dimensions dia. 75mm x D54mm
•	PS209-F	Flush mount internal (PDL style) piezo. (114dB & 200mA @ 12VDC. Dimensions L114mm x W70mm x D57mm



КS50

Outdoor high speed siren (120dB A weighted & 1.2A @ 12V)







White External siren / strobe 10-15 VDC 250MA Max. Compatible with the EC range



Charcoal External siren / strobe 10-15 VDC 250MA Max. Compatible with the EC range



High power siren with battery backup & flash light, battery included. 13.6 - 14.4VDC constant supply voltage 250mA (max) @ 128dB. Dimensions 280mm x 195mm x 95mm





	OPT-FLX-S-ST	Pet Friendly Passive Infrared Detector with Digital Quad Zone Logic
Detection	OPT-FLX-S-DT-X5	Combination PIR & Microwave Detector 10.525GHZ & Pet Friendly
Ŏ	OPT-FLX-CW-G2	FLX series wall or ceiling mount bracket CW-G2
	OPT-FLX-P-ST	Passive infrared detector with 15m wide coverage with multiple mounting options (with bracket: wall, corner ceiling)
	OPT-FLX-P-DT-X5	Professional model (10.525GHz) suitable for Commercial & Professional applications. 15m 85" wide & 24m narrow adjustable dectecion lens
	OPT-AP-360B(C)	Indoor recessed mount 360° hard-wired detector. Hole cut- out size: 45mm
	OPT-AP-20NB(C)	Indoor recessed mount hard-wired curtain detector. Hole cut-out size: 45mm



OPT-LX-402	Outdoor Passive Infrared Detector IP54
ОРТ-СХ-702	Passive Infrared Indoor Detector for Harsh Environments
OPT-CA-1W	Multi Angle Wall mount bracket for CX-702 series
OPT-CA-2C	Multi Angle Ceiling mount bracket for CX-702 series
OPT-FX-360	Cost Effective 360° Ceiling Mount Passive Infrared Detector
OPT-SX-360Z	360° Ceiling Mount Passive Infrared Detector 18m Diameter Coverage
OPT-APX-360	360° Ceiling mount indoor passive infrared detector
OPT-VXI-ST	Outdoor PIR with Spot & Area Detection and Double Conductive Shielding IP55
OPT-WXI-ST	180° Panoramic Outdoor Detector IP55
OPT-VIBRO	Intelligent Microprocessor Controlled Shock Sensor



OPT-AX-200TN	Short range Photoelectric Twin Beam 60m, IP65
OPT-AX-70TN	20m outdoor (IP65) short range photoelectric detector with lighting & surge protection
OPT-AX-100TFR	30m outdoor battery operated dual beam
OPT-AX-130TN	40m outdoor (IP65) short range photoelectic detector with lighting & surge protection
OPT-BXS-ST	Outdoor Boundary Detector with Quad PIR Sensors 2 on each side of the detector (up to 40ft Detection per side) IP55
OPT-FA-3	Multi-angle wall/ceiling mount bracket for FMX detectors
OPT-HX-40	High mount outdoor detector with active IR digital anti- masking function and intelligent detection logic
OPT-VXI-R	Battery Powered 12m outdoor PIR for Spot & Area Detection with Pet Tolerance
OPT-VXI-DAM-X5	Outdoor PIR & Microwave 10.525GHZ Detector with Anti- Masking IP55

OPT-HX-80N	High mount outdoor (IP55) PIR 24m x 2m narrow coverage with advanced temperature compensation logic
OPT-LX-802N	Outdoor passive infrared 80" narrow long range detector (IP54) with selectable detection patterns (pet alley or multi-level)
ОРТ-ОМ-106С	Microwave access control sensor (IP54), mounting height up to 3.5m
OPT-OS-12C	The Optex OS-12C active infrared safety beam system is compatible with any type of automatic door
OPT-HX-40DAM	High Mount Dual PIR & Microwave Detector 10.525GHZ for Exterior Use IP55
ОРТ-SH-7МС	For the OS-12C: 1 Pair Sensor Heads & 23' Cable
OPT-QXI-ST	Wide Angle Passive Infrared Outdoor Detector with Selectable Mounting Height & Pattern
OPT-FTN-ST	Compact outdoor detector: enhanced pet immunity, super multi dimension analysis logic & double conductive shielding
OPT-FTN-R	Multi-purpose compact outdoor detector. Battery operated with selectable detection ranges. Note: Requires CR-123AW & INFINITY INPUT (sold separately)

Detection


OPT-QXI-DT-X5	Combination PIR & Microwave Wide Angle Passive Infrared Outdoor Detector 10.525GHz
OPT-SL-200QN	60m outdoor quad photoelectric detector with Sniper Viewfinder (IP65)
OPT-SL-650QN	Outdoor 200m Photoelectric Detector IP65, includes Quad Beam with Aspherical Lenses
OPT-SL-350QFR	100m outdoor quad photoelectric detector with Sniper Viewfinder (IP65)
SWAN QUAD	Quad element pet friendly PIR, rated up to 25kg. Optimum mounting height 2.1m. Wide angle lens, detection range 18m & mounting bracket available
SWAN QUAD N/O	Quad element pet friendly PIR with normally open contacts. Ideal for use with car alarms
CRGB PLUS	Shock and/or breakage selectable. Sensitivity adjustment. Ceiling or wall mount
QUIP-1000	Microwave pet friendly PIR, rated up to 25kg. 10.525GHz with optimum mounting height of 2.1m
SWAN BKT	Wall mount bracket for the SWAN QUAD, offers a 90 degree swivel for the PIR



-	SWAN PGB	Pet friendly PIR, rated up to 25kg with built in shock & glass break detector. Optimum mounting height of
	CRTL360	Ceiling mounted 360 degree PIR. Max installation height 3.6m & max coverage dia. 20m. Dimensions dia. 110mm x D40mm
Yanad	B-PUPILLA.T	12-24V AC/DC surface mount point to point beam, with 20-25m range. Dimensions L113mm x W35mm x D30mm. IP44 rated
	B-KREX	Photoelectric retro-reflective safety beam, AC/DC 24- 240V
	B-PUPILLA XP20D	24V AC/DC surface mount point to point beam, battery powered on one side (battery not included)
	MD2010	Loop metal detector 12 - 24VDC or 16 - 24V AC. Delivers precise vehicle detection when accompanied with an in ground loop. No remote or keypad required
2	A-PROBE KIT	AAP ground probe kit for vehicle detection. Kit includes 1x A-PROBE with 25m pre-made IP rated cable & 1x A-CONTROLLER
9	A-PROBE	AAP ground probe for vehicle detection. Requires A-CONTROLLER. Dimensions dia. 34mm x L440mm
	A-CONTROLLER	Dual Channel Ground Probe Controller 12-24VAC/DC
0	GM730	Siemens seismic detector, perfect for mounting on safes. Dimensions L89mm x W89mm x D23mm













Surface Mount Reed Switch (NC) - Suitable for Doors & Windows with sensing gap 15-20mm/20-25mm (white)






HC-31

Surface Mount Reed Switch (NO/NC/COM) - Suitable for Doors & Windows. Sensing Gap 15-25mm (black)



Flush Mount Reed Switch (NO/NC/COM) - Suitable for Doors & Windows with 15 - 20mm Sensing Gap (white)



Flush Mount Reed Switch (NC) - Suitable for Steel Doors. Sensing Gap 25 - 35mm (black)



	HC-38C	Surface Mount Reed Switch (NO/NC/COM) - Suitable for Doors & Windows. Sensing Gap 15-20mm (white)
0 0	HC-39	Surface Mount Reed Switch (NC) - Suitable for Residential Windows with 15-25mm Gap (white)
Þ	HC-41	Flush Mount Reed Switch (NC) - Suitable for Doors & Windows. Sensing Gap 15-20mm (white)
	НС-45	Surface Mount Reed Switch (NC) - Suitable for Commercial

HC-46	Surface Mount Reed Switch (NC) - Discrete Size with Sensing Gap of 15-20mm (white)
-------	---

Doors with Sensing Gap of 15-20mm (white)





Reed Switches

HC-45

HC-56

Surface Mount Reed Switch (NC) - Suitable for Garage Doors with 50-70mm Sensing Gap (Zinc-Alloyed)









INFINITY REMOTE Infinity series 2 way wireless remote kit which includes: 1 x INFINITY LINK & 2 x INFINITY REMOTE



Infinity series 2 way wireless 4 button remote with haptic **INFINITY REMOTE** feedback 916Hz, compatible with EC series (requires **INFINITY LINK)**

Q	INFINITY PANIC	Infinity series 2 way wireless 1 button pendant with haptic feedback 916Hz, compatible with EC series (requires INFINITY LINK) or standalone (requires INFINITY OUTPUT)
---	----------------	--

INFINITY TX-1 Infinity series 2 way wireless 1 button weather proof remote with haptic feedback 916Hz, compatible with EC series (requires INFINITY LINK) or standalone (requires INFINITY OUTPUT)	
--	--




Wireless single channel transmitter in box 916Mhz (note: compatible with EC control panel and INFINITY OUTPUT)





COCAL/MK COCAL/MK Proje to Antonio Proje to Antonio RELEGENCE ANTONIO	GLT43301	1 channel 433Mhz handheld transmitter. Includes 9V alkaline battery
	GLT43302	2 channel 433Mhz handheld transmitter. Includes 9V alkaline battery
	GLT43304	4 channel 433Mhz handheld transmitter. Includes 9V alkaline battery
	CI T/ 7700	8 channel 433Mhz handheld transmitter. Includes 9V alkaline





GLR43301

1 channel 433Mhz receiver, compatible with the GLT series 12 - 24V



EU PALIE	
÷	
12.54	@##33
	11111

2 channel 433Mhz receiver, compatible with the GLT series 12 - 24V

GLR43304	4 channel 433Mhz receiver, compatible with the GLT series 12 - 24V



GLR43308 12R

GLR43302

8 channel 433Mhz receiver, compatible with the GLT series 12 - 24V. Includes relay outputs

ANT433M

433Mhz antenna for Gigalink series transmitters & receivers. 94cm long with cable & SMA connector



433Mhz antenna for Gigalink series transmitters & receivers. 35cm long with cable & SMA connector





MCT91516

16 channel 915Mhz multicode transmitter, compatible with the MCR series



FOB43301WP	Elsema 1 Channel Waterproof PentaFOB Transmitter with 5 Frequencies
FOB43302WP	Elsema 2 Channel Waterproof PentaFOB Transmitter with 5 Frequencies

Elsema 4 Channel Waterproof PentaFOB Transmitter with 5

FOB43304WP



Frequencies











Monitoring & Cellular

	EC IoT	Plug on EliteCloud App module for EC-PCB (note: you will also need to download EliteCloud app)
$\textcircled{\begin{tabular}{ c c c c c } \hline \hline$	EliteCloud	Available from the app Store or Google Play (requires EC-IoT module). Please note: the app for this device has paid subscription services: www.elitecloud.co.nz
	EC-i DIALLER	Plug on dialler for EC-PCB, land-line & third party monitoring
	ANT-MB-49A	500mm 7 band 7dBi whip antenna with magnetic base. 3m cable SMA 824-960/1710-1990/2170Mhz
	MEDI BRACELET	4G/3G Medical bracelet with 2-way voice & GPS tracking
	FWT 3G/4G	3G/4G GSM Cellular Unit (EC-25AU Cellular Modem)
	IoT-MODULE	EliteCloud App Module for ESL, Elite S, Elite S-Lite & Runner Control Panels
	4G-IP-MODULE	4G Universal PSTN to DATA Communicator for IP- Monitoring





Access Control







 PW KEYPAD-XK1	Standalone stainless steel outdoor keypad (IP65). 12 -24V with built in prox reader. Dimensions 115mm x 75mm x 22mm
PW KEYPAD-XK4	Standalone stainless steel outdoor keypad(IP65). 12 -24V with built in prox reader. Dimensions 134mm x 56mm x 21mm

EC-A2 REX	2 Door Access Control Module for EC & EC-i systems only

24680 * 4	PW WIEGAND	Outdoor keypad reader with built in prox/pin (IP66). 40 bit wiegand white backlit keypad, compatible with the EC-A2 REX
f	PW WIEGAND KIT	2 door access control kit, includes 1x PW WIEGAND & 1x EC-A2 REX interface board. Compatible with EC security systems











2 door access control kit, includes 1x PW WIEGAND-SK1 & EC-A2 REX interface board. Compatible with EC control system





outdoor ready and compatible with EC-A2 REX






Cable protector with metal box ends (stainless steel). 8mm dia. 300mm length




	BLE LOCK	Compact module with most secure digital access control for all premises (Wifi, Bluetooth, RFID Card, Card payment & Pin Code relay output)
6266438628	PROX CARD	Proximity card compatible with the PW & EC control system keypads. Dimensions L86mm x W54mm x 1mm
		Duraning its struggly law to a (labor). Comerciatily law its DM/ 0

PROX EM4100

Proximity tumbler keytag (blue). Compatible with PW & EC series keypads







AT2-PCB

Universal timer board 5V -30V DC with 9 selectable time modes. Dimensions 63 x 37 x 20mm





Multi function capacitive exit button for egress in access control applications. 10-28VDC 50mA current draw

	ulti function mechanical exit button for emergency egress in cess control applications. 10-28VDC 50mA current draw
--	---



REMOVE COVER TO OPERATE PALLHORE	AAP-COVER	Protective cover for the AAP-EM	
PANIC			

PANIC autor not activate	AAP-PANIC	Latching panic plate, with DPDT 2A contacts, buzzer and back light. 10-28VDC 50mA current draw
PRESS TO EXIT	WES 1910	Small stainless steel press to exit push button. Flush IP65, includes WEB1910 push button & WEBS19 face plate

PRESS	WEL 1911	PDL stainless steel blue illuminated exit push button. Flush IP65, includes WEB1911 push button & WEBL19 face plate
-------	----------	---

	PRESS TO EXIT	WEL2220	Stainless steel exit push button with mushroom green push button. NO/NC contacts	
--	------------------	---------	--	--



WEL-SMB

Outdoor	surface	mount	exit	button	with	LED	indicator.
Dimensic	ns H60m	m x W30)mm :	x D26mn	٦		









12/24V mortice lock - Fail safe/Fail secure 60mm back-set



 \bigcirc

FSHFEL990M

FSHR40-12ARM Armature plate only for FSH door holders



FSHR40-12 12V 25Kg door holder - Wall mount





- 1	YM-180W	180Kg 12/24VDC weather resistant magnetic clamp for pedestrian gates
	FSHFEM3500M	280Kg single magnetic lock - monitored
	FSH- FEM4700FS-LSS	380Kg single magnetic lock - weather resistant - monitored
	FSHFEM3500DM	560Kg double magnetic lock - monitored
	FSHFEM5000G	630Kg single magnetic lock - weather resistant
	FSHFEM5700M	580Kg single magnetic lock - monitored
	FSHFEM5700DM	500Kg double magnetic lock - monitored
	YM-280DS	280Kg 12/24VDC single door magnetic clamp

FSHR40PCH-12 12V 25Kg door holder - wall mount with extension

ABK-280GZ	GZ Bracket for Frameless Glass Door for YM-280DS
ABK-280ZLC	ZLC bracket for inward doors use with YM-280DS
FSHFEM3500FM	280Kg single flush mount magnetic lock
FSHFES10	12/24V electric strike lock - weather resistant - ANSI IP56
FSHFES20	12/24V electric strike lock - high security for commercial premises
ABK-180ZL	Weather resistant ZL bracket, compatible with the YM- 180W
FSHAMZB4-LP	ZL bracket for single mag lock, suits: FEM3500,3500M,4700FS
FSHAMZBI-LPDSS	ZL bracket for single mag lock suit: FEM5700M
Mar FSHIRT881SSS	Recessed cable transfer for mortice locks 300mm








DoorBird Technology meets Design. | EliteConnect

Intercoms











E-CON GATE	Black outdoor gate station, surface mount, 2MP 1080P. Compatible with E-CON MONITORS
E-CON GATE SA	Black standalone outdoor gate station, 2MP 1080P, Wifi & Ethernet compatible
E-CON GATE-K	Black outdoor gate station with keypad, surface mount, 2MP 1080P. Compatible with E-CON MONITORS
E-CON MONITO	DR-B Black 7" touch screen monitor with Wifi & Ethernet. Compatible with E-CON GATE & EC-CON GATE-K




White 7" touch screen monitor with Wifi & Ethernet. Compatible with E-CON GATE & EC-CON GATE-K



Video door station & colour video monitor kit which includes E-CON GATE & E-CON MONITOR-B



Intercoms



Also available in black (DB-A1101-B)



Arrowhead Alarm Products

Г <u>з</u> ,	DB-A8003	Optional table stand for IP Video Indoor Station DB-A1101 Also available in black (DB-A8003-B)
	DB-D2101KV	IP video door station with smartphone push. Stainless steel flush edition with integrated access keypad
	DB-D2101KV HOUSE V4	Surface mount housing box for DB-D2101KV & DB-D2101KV V4 IP Intercom (Salt Water Version)
	DB-D2101KV V4	IP video door station with smartphone push. Stainless steel flush edition with integrated access keypad (Salt Water Version)
• 12	DB-D2101KH	IP Video Door Station D2101KH for single family homes, stainless steel V2A, brushed, 1 call button incl. stainless steel plate with bell symbol
• 12	DB-D2101IKH	Doorbird IP Intercom Video Door Station with Keypad (V2A) Flush Mount Illuminated
	DB-D2101KH Housing-Flush	Flush-mount housing (backbox), stainless steel V2A, compatible with DB-D2101KH
	DB-D2101KV HOUSE-F	Flush Mount Housing for DB-D2101KV (Housing/Backbox)
	DB-D2102V	IP Video Door Station Stainless Steel V2A Brushed with 2 Call Buttons



	DB-A1121-S	Surface mount IP Access control Keypad Surface Mount Brushed V2A, Wiegand Interface
	DB-D2101V	IP video door station. Flush Stainless Steel Brushed V2A. Includes 1x call button
	DB-D21DKH	IP video door station, brushed stainless steel, flush mounted (Horizontal), display module, keypad module. Enquire for stock availability
	DB-D21DKV	IP video door station, brushed stainless steel, flush mounted (Vertical), display module, keypad module. Enquire for stock availability
	IT-Wifidoorbell	4MP Wifi/smart Doorbell with AI for Indoor/outdoor applications
	DB-A1071	2-Wire Ethernet POE converter compatible with DoorBird intercoms
	DB-A1061W	IP internal door chime compatible with DoorBird IP intercoms. White edition. Note: lead time may apply
	AAP GOOSE NECK	Polished Stainless Steel Goose Neck Plinth for Intercom Gate Stations & Keypads - Mount in Concrete
Ŋ	WELL-LPV-20-15	15V 1.3A switch mode power supply in IP67 case. 100 - 240VAC input. Dimensions L116mm x W34mm D27mm





For custom colour requests on the DB range contact our Sales Team for more information: Email: sales@aap.co.nz Phone: (09) 414 0085

Choose Your Colour!



RAL 1001	RAL 1003	RAL 1004
beige	signalgelb / signal yellow	goldgelb / golden yellow
RAL 1016	RAL 1017	RAL 1037
schwefelgelb / sulfur yellow	safrangelb / saffron yellow	sonnengelb / sun yellow
RAL 2002	RAL 2004	RAL 3000
blutorange / vermilion	reinorange / pure orange	feuerrot / flame red
RAL 3007	RAL 3014	RAL 3028
schwarzrot/ black red	altrosa / antique pink	reinrot / pure red
RAL 4004	RAL 4005	RAL 4006
bordeauxviolett / claret violet	blaulila / blue lilac	verkehrspurpur / traffic purple
RAL 4009	RAL 5002	RAL 5004
pastellviolett / pastel violet	ultramarinblau / ultramarine blue	schwarzblau/ black blue
RAL 5012	RAL 5013	RAL 5018
lichtblau / light blue	kobaltblau / cobalt blue	türkisblau / turquoise blue
RAL 5022	RAL 6000	RAL 6006
nachtblau / night blue	patinagrün / patina green	grauoliv / grey olive
RAL 6018	RAL 6019	RAL 6027
gelbgrün / yellow green	weißgrün / pastel green	lichtgrün / light green
RAL 7001	RAL 7004	RAL 7006
silbergrau / silver grey	signalgrau / signal grey	beigegrau / beige grey
RAL 7011	RAL 7015	RAL 7016
eisengrau / iron grey	schiefergrau / slate grey	anthrazitgrau / anthracite grey
RAL 7023	RAL 7033	RAL 7044
betongrau / concrete grey	zementgrau / cement grey	seidengrau / silk grey
RAL 8004	RAL 8011	RAL 8016
kupferbraun / copper brown	nussbraun / nut brown	mahagonibraun/ mahogany brown
RAL 8023	RAL 8028	RAL 9002
orangebraun / orange brown	terrabraun / terra brown	grauweiß / grey white
RAL 9006	RAL 9007	RAL 9010
weißaluminium / white aluminium	graualuminium / grey aluminium	reinweiß / pure white
RAL 9016 verkehrsweiß / traffic white	DB 703 Eisenglimmer / pearled dark grey	

* The listed colours above are not binding. For the exact colour determination we recommend a valid RAL colour register *





Gate Automation







B-BULLTURBO-KIT	Kit includes 24V B-BULL624 TURBO sliding gate motor & controller, 2x B-TO.GO2VA & 4x B-197.1 nylon racking
B-BOB3024E.P-BK	Kit includes 24V 2x B-BOB3024E screw drive actuators, B-BRAINY24 controller, B-PUPILLA.T & 2x B-TO.GO2VA remotes
B-BOB3024E	24V screw drive actuator with mechanical stops. Requires B-BRAINY24 and used for gates up to 3m leaf. Intensive use duty cycle, 1800N thrust
B-BSR	Adjustable mounting bracket for linear actuators. Compatible with the B-BOB30 series
B-BOB5024	24V screw drive actuator with mechanical stops. Requires B-BRAINY24 and used for gates up to 5m leaf. Intensive use duty cycle, 2200N thrust
B-BACK UP SWING	Battery Back Up kit for Beninca 24V gate automation, compatible with B-BOB3024E & B-BOB5024
B-PR45E24	24V hinge arm with built in limit switches. Arm not included, you require B-DUE2 and used for gates up to 3m leaf. Intensive use duty cycle, 320Nm torque



B-DUE2		alvanised steel hinge arm for articulated arm tuators. Compatible with B-PR45E & B-PR45E24
Restrict Control of the second		attery Back up kit for Beninca 24V Sliding Gate atomation, compatible with B-BULL1224
B-BACK SLIDE-6		attery Back up kit for Beninca 24V Sliding Gate atomation, compatible with B-BULL624TURBO
B-BULL		VDC sliding gate motor for gates up to 600kg & 25m/ in. Includes built in limit switches & receiver/controller
B-BULLI	224 су	V sliding gate motor for gates up to 1200kg. Duty cle 80% with 390N max thrust. 115VAC/230VAC power pply. 3A max absorbed current
B-BISON	1250TI bu	OV sliding gate motor for gates up to 2500kg with all in limit switches. Built in controller & receiver with censive duty cycle
B-EVA.7		ad barrier control unit with integrated receiver, for ussages up to 7m
B-EVA7	A /	inted elliptical aluminium arm cut into two 3.5m ction
AAP E-L	.OOP KIT R Re	esidential Wireless Gate Sensor
AAP E-L REMOT		otional Diagnostic Tool for AAP E-LOOP KIT R & AAP LOOP KIT C



	AAP E-LOOP KIT C	Commercial Wireless Gate Sensor
Commercial and	B-BOB-RELEASE	Release lever for the B-BOB3024E actuator
((iii	B-MLS	Magnetic Limit Switch kit for sliding gate actuators
	B-ONE.2WB	433Mhz 2 channel universal receiver in a box compatible with Beninca remotes (both 2 & 4 button)
	B-CP.B24ESA	24V Controller for B-BULL624TURBO
	B-ADVANTOUCH	Advantouch Programmer for Beninca Control Panels
	B-311.M	Adjustable bracket for B-311.M end catch
	B-310.M	80mm End Catch for Sliding Gates
	B-230.1	150mm x 40mm Single Roller - add to B-213.3B for Installations on a Gradient
E THE	B-199.1	Hydraulic Radial Damper

Gates



and an and a second	B-197.1	Nylon racking for Beninca sliding gates. Dimensions L1000mm x W28mm D22mm. Compatible with B-BULL motors
Sort Sort And	B-192.1	Metal racking for Beninca sliding gates. Dimensions L1005mm x W30mm x D12mm. Compatible with B-BULL motors. Spacers sold separately
ł	B-192.1 Spacer	Metal spacer to go with the B-192.1 racking. Note you require 3 spacers for 1 x B-192.1
ł	METAL PIN	Metal pin anchor for B-192.1 racking. Dimensions 6.5mm x 50mm
	B-SIS KIT	Bus module for synchronizing gate controllers (2 x B-SIS modules)
	B-186.3	3m U-Section 16mm gate tracking for sliding gates. Compatible with 20mm wheels and the B-BULL motors. Note: oversized freight cost may apply
50.	B-111.80	80mm U-Section gate wheels (20mm). Compatible with the B-BULL motors
	B-111.100	100mm U-Section gate wheels (20mm). Compatible with the B-BULL motors
ŀ	B-213.3B	2 roller guide plate (bolt on). Compatible with sliding gate motors
	B-417.20	Swing gate hinge, adjustable 70mm wide with 20mm thread. Compatible with swing gates

Gates



	B-247.2	Bolt down end stop for Beninca swing & slide gate motors
	B-530.0	Gate stops to be cemented for swing gates. Compatible with B-BOB & B-BILL swing actuators
	B-535.2	Gate stop for B-BOB swing gates (bolt on)
BOOMCA 1 2 3 4 5 6 7 8 9 0 mm	B-BE.CODE	Wireless keypad for controlling automated systems. Max 254 different codes linking the device to your receiver
2	B-DU.FCN	Waterproof limit switch device for DU.IT24 underground actuator series
	B-DU.ITIX	Self supporting stainless steel foundation box, max opening of 110 degrees. Comes only with cover, requires an unlocking accessory
Control of the second	B-DU.IT24NVE	24V underground motor for swing gates up to 3.5m. Built in encoder to ensure maximum safety & precision in the gate moving phase
	B-KEY	Master keys for Beninca motors, key range from 1171 - 1180 (pack of 10)
Q	B-IRI.LAMP	Universal LED flashing light. Also comes with blinking function as standard. Includes inbuilt aerial
	B-SC.M72	Mechanical Safety Edge 2 Metres




	B-BOB.BUSH	Whole bush for the B-BOB screw drive actuator series
Innes	B-PUPILLA.T	12-24V AC/DC surface mount point to point beam, with 20-25m range. Dimensions L113mm x W35mm x D30mm. IP44 rated
	B-PUPILLA XP20D	24V AC/DC surface mount point to point beam with battery on one side of the beam
	B-FTC.S	24V AC/DC safety beam set. Fits in commercial sliders including B-BISON. Dimensions L90mm x W75mm x D30mm
	B-POL.05	Pair of disassembled columns, not premounted, equipped with base and bracket for PUPILLA photocells. H = 0.5m
	B-CBY.24V	Battery charger card for CBY.24V, bracket not included. Used for battery charging
Januar Contraction of	B-BRAINY BOX	Plastic box only for Brainy controller. Dimensions L285mm x W220mm x D120mm
	B-BRAINY24 PCB	BRAINY24 control panel for 24V actuators (PCB only)
	B-BRAINY24+	24 V/DC Controller with integrated receiver and battery charger (64 Remote Slots) - Dimensions 285 x 220 x 120mm

B-SA-24	27VDC Beninca power supply with battery backup
B-TO.GO4AK	4 channel 433Mhz transmitter which is cloneable. Compatible with Beninca actuators
B-TO.GO2VA	2 channel 433Mhz transmitter with advanced rolling code. Compatible with Beninca actuators
B-TO.GO4VA	4 channel 433Mhz transmitter with advanced rolling code. Compatible with Beninca actuators
B-SMART	Turn your transmitter into an elegant wall mounted keypad. Can be fixed to the wall and it is compatible with all B-TO.GO remotes
B-TO.CLIP	Plastic clip for B-TO.GO remotes. Suitable for use on your car visor or wall
B-ANT433	433Mhz extension antenna for Beninca controllers. Compatible with B-TO.GO remotes & controllers
B-Viro	12V Strike for swing driveway & pedestrian gates & 35mm lock Cylinder (vertical mount)
B-Viro-Horizontal	12V Strike for swing driveway & pedestrian gates & 35mm lock Cylinder (horizontal mount)

Arrowhead Alarm Products





Page 56

HM-SMOKE230	230V hardwired smoke alarm with 9V DC alkaline battery backup & inter-connectable
FMR-100	Flush mount ceiling ring for NB338 & NB323 smoke detectors. Hole cut-out size 110mm
NB338-4ARB	12V resetting smoke detector with buzzer & hush button. Compatible with the EC security system
NB323	Rate of Rise thermal heat detector. Trigger temperature 57 degrees & compatible with the EC security system



12V smoke detector, latching with buzzer (no hush button). Compatible with the EC security system



Aerosol smoke detector test can for HM & NB smokes



Fire



DM12-1.3PP	PowerPac 12V 1.3A battery. Dimensions L100mm x W45mm x D52mm
DM12-2	PowerPac 12V 2A battery. Dimensions L170mm x W60mm x D35mm
DM12-3	PowerPac 12V 3A battery. Dimensions L133mm x W68mm x D60mm
	DowerDag 12)/ 54 battery, Dimensions L00mm x 14/101mm x
DM12-5A/H	PowerPac 12V 5A battery. Dimensions L90mm x W101mm x D70mm

Participan and a series	DM12-7.5	PowerPac 12V 7.5A battery. Dimensions L150mm x W65mm x D95mm	



DM12-9

PowerPac 12V 9A battery. Dimensions L150mm x W65mm x D95mm





-

DM12-12

PowerPac 12V 12A battery. Dimensions L150mm x W100mm x D100mm

PowerPac	DM12-18PP	PowerPac 12V 18A battery. Dimensions L180mm x W75mm x D165mm	
PowerPac	DM12-22AH	Powerpac S.L.A battery 12V 22A. Dimensions 181 x 77 x 166mm	

PowerPac	DM12-40	PowerPac 12V 40A battery. Dimensions L175mm x W195mm x D165mm
----------	---------	--

	DM6-5A	PowerPac 6V 5A battery. Dimensions L46mm x W70mm x D105mm
--	--------	--

	1/2 AA 3.6V lithium battery
--	-----------------------------







+ CR 1220 CR1220	3V Lithium Battery Round Coin Cell
CR2 BATTERY	3V Lithium Battery CR2 (Compatible with B-PUPILLA XP20D)
CR2016	Coin cell lithium battery 3V
CR2032 CELL	Coin cell lithium battery 3V
CR2450	Coin cell lithium battery 3V
142-004	A23 12V miniature battery, dimensions L28mm x Dia. 10mm
A27	A27 12V alkaline battery, dimensions L28mm x Dia. 8mm
142-006	9V alkaline battery, dimensions L48mm x W48mm x D26mm
BC-12500	Battery charger for DM PowerPac batteries, 12V & 800mA







4C2-100-CU

4 core 0.2mm tinned copper cable with box centre pull. Comes in 100m roll

4C5-100-CU


4C5-300-CU

6C5-100-CU

4 core 0.5mm tinned copper cable with box centre pull. Comes in 100m roll

-	0 810,		
		21	


4 core 0.5mm tinned copper cable with drum centre pull. Comes in 300m roll





6 core 0.5mm tinned copper cable with box centre pull. Comes in 100m roll







8 core 0.5mm tinned copper cable with drum centre pull. Comes in 300m roll











2.1mm DC female plug with DC terminal connector used for CCTV







Universal timer board 5V -30V DC with 9 selectable time modes. Dimensions 63 \times 37 \times 20mm



12V 1A SPDT relay board, dimensions L43mm x W39mm x D18mm



DPDT 8 Amp Relay board, with 12V or 24V AC/DC Coil + Low Current Pos/Neg Trigger Mode








EC-CAB

Plastic cabinet for EC system. Holds 12V 7.5A battery, supports 1.4A power supply & multiple board locations with clip in tabs. Dimensions L323mm x W293mm x D87mm

Plastic box IP56 rated, dimensions L100mm x W100mm x D50mm







Plastic box IP65 rated, dimensions L250mm x W175mm x D103mm







PS12300EP

12V DC 500mA plugpack. Can be used for many applications including powering keypads & transmitters etc



Switch mode in-line powerpack 12V DC 4A, used to power CCTV cameras



TEPP16V

Plugpack 16V AC 1.5A, used to power EC security system







DC CONV-5

Mini AC/DC converter, 16 - 28V in to 12V DC out 500mA. Dimensions L74mm x W40mm D23mm



B-SA-24

27VDC Beninca power supply with battery backup





PSU1 SM

13.8V 1.5A Plated Power Supply with Monitor Outputs. Dimensions L200mm x W92mm x D60mm





13.8V 6A (battery backup) in Plastic Cabinet, Smart Compatible with: EC-A2, EC-O4 & EC-Z8



15V 1.3A switch mode power supply in IP67 case with 100 - 240V AC input. Dimensions L116mm x W34mm x D27mm



12V 1.5A switch mode power supply in IP67 case with 230V AC input. Dimensions L140mm x W30mm x D23mm



FUSED BOARD-8

Safely power 8 low voltage devices from one power feed. 8 \times 1.6A fused outlets, features 2.1mm DC plug input



The second se	Drill Bits

BES-BELL1412	Diameter 6.4mm x L305mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL3812	Diameter 9.5mm x L305mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL1212	Diameter 12.7mm x L305mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL1424	Diameter 6.4mm x L610mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL3824	Diameter 9.5mm x L610mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL1224	Diameter 12.7mm x L610mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL1436	Diameter 6.4mm x L915mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-BELL3836	Diameter 9.5mm x L915mm bell hanger bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws

Drill Bits



BES-FLX1424	Diameter 6.4mm x L610mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-FLX3824	Diameter 9.5mm x L610mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
BES-FLX1224	Diameter 12.7mm x L610mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws

Diameter 6.4mm x L915mm HSS flex bit made from premium

M2 grade steel. Cuts through wood, metal, nails & screws

BES-FLX3836	Diameter 9.5mm x L915mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
-------------	--

BES-FLX1236	Diameter 12.7mm x L915mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
-------------	---

BES-FLX1454Diameter 6.4mm x L1372mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws	١
--	---

	BES-FLX3854	Diameter 9.5mm x L1372mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws
- 1		

BES-FLX1254

BES-FLX1436

Diameter 12.7mm x L1372mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws



Diameter 9.5mm x L1829mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws

BES-FLX1272

Diameter 12.7mm x L1829mm HSS flex bit made from premium M2 grade steel. Cuts through wood, metal, nails & screws

BES-QTT91648

Diameter 14.3mm x L1219mm auger flex bit, with four cutting edges allowing for rapid cutting. Crafted from high quality steel

BES-GLF415

Single 3 foot 4mm fibreglass glow rod, durable plastic coating super flexible design & perfect for a wide range of installations

BES-GLF410

Single 6 foot 4mm fibreglass glow rod, durable plastic coating super flexible design & perfect for a wide range of installations





CCTV Solutions





Protect what matters most to you!


Consider adding a CCTV system to your home or business to protect your most valuable assets. TVT has a wide range of cameras and recorders to suit most applications and needs. Each TVT system comes with a free Apple or Android app so you can stay connected from anywhere, at any time

App Functions/Screenshots









Device Settings





TVT-4CHNVR- 2CAMKIT-AI-6MP	4 Channel NVR kit includes: 1x TVT-4CHNVR-P, 2 x TVT- D28C-AI-6MP cameras, 2 x 20m CAT cables & 2TB HDD Also available with black cameras (TVT-4CHNVR-2CAMKIT-B-AI-6MP)
TVT-4CHNVRKIT AI-6MP	4 Channel NVR kit includes: 1x TVT-4CHNVR-P, 4 x TVT- D28C-AI-6MP cameras, 4 x 20m CAT6 cables & 2TB HDD Also available with black cameras (TVT-4CHNVRKIT-B-AI-6MP)
TVT-8CHNVRKIT AI-6MP	8 Channel NVR kit includes: 1x TVT-8CHNVR-P, 4 x TVT- D28C-AI-6MP cameras, 4 x 20m CAT6 cables & 2TB HDD Also available with black cameras (TVT-8CHNVRKIT-B-AI-6MP)
TVT-4CHNVR-P	4 channel 1080P NVR 4 POE port with 2TB Hard Drive
TVT-8CHNVR-P	8 channel 1080P NVR 8 POE port with 2TB Hard Drive
TVT-16CHNVR-P	16 channel 1080P 4K NVR 16 POE port with 4TB Hard Drive
TVT-32CHNVR-P	32 channel 1080P 4K NVR 16 POE port with 6TB Hard Drive
TVT-64CHNVR	64 channel 1080P NVR 16 HDD slots with 2 x 6TB Hard Drive (note: no POE)
TVT-TD-3008H1- 8P-B1	8 Channel NVR with 8 POE ports & 2TB HDD. Supports up to 6MP cameras



CCTV

· Prr	TVT-D28C-POE- 6MP-AI	6MP S4-C Full Colour 2.8mm fixed lens, dome POE camera. compatible with TVT-NVR's (IP67)
Dry	TVT-D2812POE	5MP 2.8 - 12mm motorised varifocal lens, POE waterproof dome camera. Compatible with TVT NVR's
· PT	TVT-D2812POE- 6MP-C	Full Colour 6MP Smart white light camera with electric zoom lens: 2.8~12mm. Compatible with TVT-NVR's (outdoor ready)
· PAT	TVT-D2812-8MP-AI	8MP 2.8-12mm motorised lens, waterproof dome POE camera. Compatible with TVT-NVR's
nr Ka	TVT-D2.8-B-6MP-C	6MP 2.8mm fixed lens POE dome waterproof IP camera. Compatible with TVT-NR's
О ЛТ	TVT-D722AI	2MP 7-22mm lens, waterproof Ai face recognition camera.Compatible with TVT-4CHNVR-P & 8, 16 & 32 channel models
	TVT-D2.8-F-4MP	4MP 2.8mm Fixed Lens Camera with high security flashing light. Compatible with TVT-NVR's
	TVT-D2812-F-4MP	4MP 2.8mm - 12mm Varifocal Lens Camera with high security flashing light. Compatible with TVT-NVR's
	TVT-360POE	6MP 1.07mm POE 360 degree fisheye camera with microphone. Outdoor ready. Compatible with TVT-NVR's



TVT-B2812POE- 6MP-AI	6MP 2.8-12mm motorised varifocal lens, bullet POE camera. Compatible with TVT-NVR's (outdoor ready)
TVT-B2812-8POE	8MP 2.8-12mm motorised varifocal lens POE waterproof bullet camera. Compatible with TVT-NVR's
TVT-B28SPOE	2MP 2.8mm lens, IP starlight bullet POE camera Compatible with TVT-NVR's
TVT-B722POE	4MP 7-22mm lens, bullet POE camera with 100m IR. Compatible with TVT-NVR's
TVT-B722-2POE-LP	2MP 7-22mm lens Starlight, license plate recognition bullet POE camera with 100m IR. Compatible with TVT- 8CHNVR-P & 16, 32 channel models
TVT-B832-4POE-LP	4MP 8-32mm lens Starlight, license plate recognition bullet POE camera with 120m IR. Compatible with TVT- 8CHNVR UP IP67
TVT-P180-8POE	8MP starlight 180° panoramic waterproof bullet network camera. Compatible with TVT-NVR's
TVT-PTZ-MINI	2.8-12mm lens, auto-tracking, AI, IR night mode switching to full colour on AI detection, Active Deterrent. Compatible with TVT-NVR's
TVT-PTZ-TD8443IS	4MP 4.8 - 120mm 25x optical zoom, PTZ camera with auto tracking & starlight IR 150m network 4-inch smart PTZ



CCTV



8MP 25x Starlight IR 150M Network 4 inch Smart PTZ Camera, IP66 with bracket and PSU

a 2	TVT-B2.8POE-Wifi	4MP IP bullet camera with built-in wifi capability. 20- 30m IR range, intelligent analytics and outdoor ready (IP67)
05	IT-WifiCAM	4MP Wifi/solar security camera with AI for Indoor/ outdoor applications
	IT-CUBE	2K HD (2304x1296), Wi-fi with real time human/pet monitoring, USB-C cable and charger included
	TVT-4GCAM	4MP Solar-powered 4G Full-Color Network Camera with 2.8mm Fixed Lens

Simple & Cost Effective TVI CCTV

TVT-4CHDVRKIT	4 channel DVR, 4x 3.6mm 1080P dome cameras, 4x 20m coax cables, 1TB HDD & 1x DC splitter
TVT-4CHTVR	4 channel 1080P output. TVI/AHD & CVI recorder with 1TB hard drive. Includes 4 external alarm inputs &1 alarm output
TVT-16CHTVR	16 channel 1080P output. TVI/AHD & CVI recorder with 4TB hard drive. Includes 4 external alarm inputs & 1 alarm output



Additional CCTV Products & Accessories

POE-4	4 PoE PoE long	distance switch
POE-8	8 PoE PoE long	distance switch
POE-10	6 16 PoE Power P	Port Gigabit 30W per port (10/100Mbps)
POE-24	4 24 PoE Power F	Port Gigabit 30W per port (10/100Mbps)
тут-уг		camera bracket, compatible with TVT- 2.8POE-6MP-AI & TVT-D2812POE
TVT-YX BLACK		nction Box for wall or ceiling mount, T-D2.8POE-6MP-AI
тут-ух		et junction box, perfect for hiding excess atible withTVT-D2.8POE-6MP-AI, TVT-
тут-ух		ion Box compatible with TVT-B2812TVI, VT-B922POE, TVT-D2.8POE-6MP-AI, TVT- T-P180-8POE
тут-уз	ZJ0601 Corner mounti	ng bracket for cameras
Т тут-уг	ZJ0811 Pendant brack Box	et - must be used with YZJ0302 Junction



	2MP video doorbell kit which includes: TVT-INTERCOM, TVT-MONITOR & POE-4
TVT-INTERCOM	Sleek video doorbell with 2MP camera, wide field of view achieving doorway security monitoring. Also includes access control funtions and prox ready
	7" touch screen indoor monitor suitable to be used with the TVT-INTERCOM
TVT-PROX TAG	Prox tag with keyring loop, compatible with the TVT-INTERCOM series
тут-тр-е9120	Wireless intercom chime compatible with TVT- INTERCOM
TVT-TD-YHZ0103	Surface mount bracket with sun visor (black) and compatible with the TVT-INTERCOM
TVT-TD-YZJ1007	Angle bracket surface mount (black) and compatible with the TVT-INTERCOM
TVT-TD-YHZ0102	Sunshade for TVT-INTERCOM
тут-ухноіо4	Surface mount waterproof junction box, compatible with TVT-D2.8POE-6MP-AI
тут-ухно206	Surface mount waterproof junction box, compatible with TVT-PTZ-MINI



тут-ухнозоі	Surface mount waterproof junction box (suitable for wall or ceiling) and compatible with TVT-D2.8POE-6MP-AI
TVT-YZJ0203 BLACK	Wall mount camera bracket (black/charcoal) suitable for TVT-D2.8POE-B-AI-6MP
TVT-YZJ0807	Ceiling mount bracket compatible with TVT-PTZ-MINI
ТVТ-ҮZJ0701Е	Mounting bracket compatible with TVT-PTZ-MINI
TVT-YZJ0204	Wall mount camera bracket, compatible with TVT- D2812TVI
TVT-YZJ0813	Ceiling mount camera bracket, compatible with TVT- 360POE
тут-ухно205	Camera bracket junction box, compatible with TVT- D2812TVI, TVT-D2.8TVI & TVT-D2.8POE-6MP-AI
тут-ухнозоз	Camera bracket junction box, compatible with TVT- D2812TVI
TVT-ZG0202	Extendable pole bracket 20cm length, may require additional mounting brackets based on your camera selection
TVT-YZJ0408	Wall mount camera bracket, compatible with TVT- D2812TVI. Note - may require additional accessories



тут-у	ZJ0501 bul	e mount camera bracket, compatible with dome & let cameras. Note - may require additional accessories pending on camera model
POE IN	IJECTOR 100	gle Port Gigabit POE Injector, input voltage 9-240VAC, output voltage 48VDC, data range 100/1000Mbps
SWITC	H-8 8P	ort Gigabit Non POE Switch 12V/DC
WIFI L 300P-F	R-CPE trai	ng range outdoor wireless bridge with maximum nsmission range of 1km. Supports POE solutions and g pack included
	ENDER Tra	nsmit IP camera signal over existing coaxial cables. nsmission distance of up to 220m & includes built-in ge protection
	COR 23.8	8" Flat LED monitor HDMI + VGA
BALUN		/TVIAHD over CAT6 Balun Pair up to 300m. Compact e and easy installation
WARNING SCUERAS OPERATING BLACK		ck small CCTV warning sign, PVC outdoor rated. nensions L240mm x W150mm
WARNING SECURITY CAMERAS OPERATING		ck large CCTV warning sign, PVC outdoor rated. nensions L300mm x W240mm
WARNING SECURITY OPERATING DECETV S BLACK		ck warning surveillance cameras sticker. Dimensions 0mm x W80mm
SURVEILLANCE CAMERAS MAY BE OPERATING		all CCTV warning sign, PVC outdoor rated. Dimensions 60mm x W150mm

WARNING SURVEILLANCE CAMERAS MAY BE OPERATING	CCTV SIGN-L	Large CCTV warning sign, PVC outdoor rated. Dimensions L300mm x W240mm
WARNING SURVEILLANCE CAMERAS MAY BE OPERATING	CCTV STICKER	Warning surveillance cameras sticker. Dimensions L160mm x W80mm
WD Purple	HDD-2TB	Hard drive 2TB SATA Western Purple Surveillance Edition
	HDD-4TB	Hard drive 4TB SATA3 Western Purple Surveillance Edition
6	HDD-6TB	Hard drive 6TB SATA3 Western Purple Surveillance Edition



Arrowhead Alarm Products

Making every home & business smart, safe & secure

Phone: (09) 414 0085 Website: www.aap.co.nz

For all Tech Sales Enquires Jeremy Skinner: jeremy@aap.co.nz Roman Jacobs: roman@aap.co.nz

For all orders

For all Tech Support Enquires tech@aap.co.nz (09) 414 0085

🔰 1A Emirali Road, Silverdale, 0932, Auckland, New Zealand

Sales Manager - Matt Hobson matt@aap.co.nz 027 588 9844

Lower North Island Sales Representive - Mark Kidd-Anderson

mark@aap.co.nz027 269 6602

South Island Sales Representative - Nicky Foden

🖂 nicky@aap.co.nz

022 105 3589

