

DB-D101

IP Video Door Station

Surface mount 1 button station

White Edition



www.aap.co.nz



- Video & audio communication
- Smartphone & tablet compatible
- Free app for Apple & Android
- Motion sensor with 4D technology
- Designed & manufactured in Germany
- Store images for free

 **DoorBird**
Technology meets Design.



 Download on the
App Store

 GET IT ON
Google Play

DB-D101 Technical Specifications

GENERAL

Housing	Polycarbonate, UV-resistant
Doorbell button	Stainless-steel button with illuminated LED ring
Mounting type	Surface-mounted
Power supply	15 V DC (power 110 - 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	271 g
Connectors	Power, electric door opener/strike, door chime, door opener button, network
Weather protection	Yes, IP65
Approvals	IP65, CE, FCC, IC, RoHS, REACH, IEC/EN 62368, IEC/EN 62471
Dimension	157 x 75 x 35 mm (H x W x D) 6,18 x 2,95 x 1,38 in (H x W x D)
Operating conditions	-20 to +40°C / -4 to 104°F Humidity 10 to 85% RH (non condensing)
Scope of delivery	Video Door Station, mounting plate, power supply unit (world-wide, 110 - 240 V), DIN-rail power supply sold separately, screw package, quick start guide
EAN	4260423860001
Warranty	see www.doorbird.com/warranty

CURRENT SYSTEM REQUIREMENTS

Mobile device	Latest iOS on iPhone/iPad, latest Android on Smartphone/Tablet
Internet	High-Speed landline broadband internet connection, DSL, cable or fiber, min. 500 kbs uploadbandwith, no socks-or proxyserver
Network	802.11 b/g/n 2.4 GHz or Ethernet network, with DHCP
Recommended	Camera lens should be at a min. height of 145 cm (57 in). Before the installation

VIDEO

Camera	HDTV 720 p, dynamic (VGA - HDTV)
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs

AUDIO

Audio components	Speaker and microphone, echo and noise cancellation
Audio streaming	Two-way duplex

NETWORK

WiFi	802.11 b/g/n 2.4 GHz
Ethernet	Connector, PoE

MOTION SENSOR

Type	Passive infrared sensor (PIR)
Detection angle	180°
Range	2 - 8 m (79 - 315 in) depends on environment

INTEGRATED WIRELESS MODULES

WiFi	2.4 GHz, external antenna
------	---------------------------

THIRD-PARTY INTEGRATION (DOORBIRD CONNECT)

Partnerintegrations	see www.doorbird.com/connect
API	see www.doorbird.com/api
Simultaneous video streams	One, for event-based and continuous recording

OPTIONAL ACCESSORIES



Proudly Supplied by AAP

344B Rosedale Road, Albany, 0632

Auckland, New Zealand

www.aap.co.nz