



DoorBird
Technology meets Design.



D2101KV

IP VIDEO DOOR STATION

Brushed Stainless Steel • Keypad Module • 1 Call button

Designed,
developed and
made in Germany

GENERAL

Front panel	Brushed stainless steel, 3 mm (0.12 in)
Mounting housing (backbox)	Stainless steel
Mounting type	Flush-mounted, surface-mounting housing sold separately
Power supply	15 V DC or Power over Ethernet (PoE 802.3af Mode-A)
Call button	Plastic. Engraveable metal cover plate sold separately, see www.doorbird.com/buy
Nameplate	Illuminated
Keypad Module	12 keys, illuminated, configurable via App, e.g.
	• Individual PIN codes
	• Individual events (e.g. switch a relay, HTTP(s) notification)
	• Individual schedules
Weight	2040g
Connectors	• RJ45, for LAN/PoE
	• Bi-stable latching relay #1, max. 1-24 V DC/V AC, 1 Ampere, e.g. for electric door opener
	• Bi-stable latching relay #2, max. 1-24 V DC/V AC, 1 Ampere, e.g. for electric door opener
	• Switch relays, max. 1-24 V DC / V AC, 1 ampere, e.g. for conventional door chimes
	• External input for external door opener button (potential-free)
• 15 V DC input (+, -)	
Weather-proof	Yes, IP65
Approvals	CE, IC, FCC, RoHS, IP65, IK08
Dimensions	349,5 x 129 x 49,6 mm (H x W x D) 13.76 x 5.08 x 1.95 in (H x W x D)
Operating conditions	-25 to +55°C / -13 to 131°F
	Humidity 10 to 85 % RH (non condensing)
Scope of delivery	1 x Main Electrical Unit
	1 x Front panel
	1 x Mounting housing (backbox)
	1 x Power supply unit (mains adaptor) with four country-specific adaptors (110 - 240 V AC to 15 V DC)
	1 x RFID key fob
	1x Screwdriver
	1x Quickstart guide with Digital Passport
	1x Installation manual
1x Small parts	
EAN	4260423862708
Warranty	see www.doorbird.com/warranty

CURRENT SYSTEM REQUIREMENTS

System requirements	Mobile device: Newest iOS on iPhone/iPad, newest Android on Smartphone/Tablet
System requirements	Internet: High-Speed Landline Broadband Internet connection, DSL, cable or fiber optic, no socks or proxy server
System requirements	Network: Ethernet Network, with DHCP

Recommended installation height Camera lens should be at a min. height of 125 cm (49 in)

VIDEO

Camera	HDTV 720p, dynamic (VGA - HDTV)
Lens	High-end ultra wide-angle hemispheric lens 180° horizontal, 90° vertical, straightened, IR-capable
Night-vision	Yes, light sensor, automatic IR-cut filter, 12 IR-LEDs (850 nm)

AUDIO

Audio components	Speaker and microphone, echo and noise cancellation (AEC, ANR)
Audio streaming	Two-way, full duplex

NETWORK

Ethernet	RJ45 jack, PoE 802.3af Mode-A
----------	-------------------------------

MOTION SENSOR

Type	Active
Detection angle	110°
Range	1 - 10 m (3.3 - 32.9 ft), depends on environment, configurable in 1 m (3.3 ft) steps.
Technology	4D. Based on multiple integrated sensors and algorithms, e.g. Radio Frequency Energy (RFE)
Configuration	Via App, e.g.
	• Range (1.10 m / 3.3 - 32.9 ft)
	• Movement direction (coming, leaving, both)
	• Individual events (e.g. switch a relay, push notification, SIP call [audio/video], HTTP(s) notification)
• Individual schedules	

RFID

Type	Active Reader Passive Tag (ARPT) system
Standard	ISO/IEC 18000-2:2009 Part 2, EM4100, EM4102
Frequency	125 KHz
Range	0 - 3 cm, depends on environment
Antenna	Internal
Compatible Transponder	RFID key fobs, sold separately, see www.doorbird.com/buy
Compatible Transponder	Up to 100 tags manageable
Configuration	Via App, e.g.
	• Tag (add, delete)
	• Individual events (e.g. switch a relay, push notification, SIP call [audio/video], HTTP(s) notification)
	• Individual schedules

INTEGRATED WIRELESS MODULES


RFID	125 KHz
Sensor	24 GHz, can be disabled

OPTIONAL ACCESSORIES


Sold separately	see www.doorbird.com/buy
-----------------	--

Special remarks:
Assembly requires professional skills or a technician.


Front panel material thickness: 3.0 mm (0.12 in)



Front panel




Flush mounting housing



Flush mounting housing

Flush mounting housing



Flush mounting housing