


CAMERA

TD-9565S4

6MP IR Water-proof Turret Network Camera



- H.265+ /H.265 /H.264+/H.264/MJPEG coding
- Starlight
- Max.resolution:6MP (3072 × 2048)
- ICR auto switch, true day / night vision
- 3D DNR, WDR, HLC, BLC, smart IR, etc.
- ROI coding
- 30~50m IR night view distance
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Intelligent analytics



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Specifications	Model	TD-9565S4		
Camera				
Image Sensor		1 / 2.7 "CMOS		
Image Size		3072 × 2048		
Electronic Shutter		1 / 1s ~ 1 / 100000s		
Iris Type		Fixed Iris		
Min. Illumination		0.007 lux @F1.6, AGC ON; 0 lux with IR		
Lens		2.8~12mm@F1.4, motorized		
Field of View		Horizontal: 100°~36.5°; Vertical: 52°~20.5°; Diagonal: 116°~41°		
Lens Mount		Ø14		
Day&Night		ICR		
Wide Dynamic Range		120dB		
BLC		Yes		
HLC		Yes		
Digital NR		Yes		
Angle Adjustment		Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360°		
Image				
Video Compression		Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG		
H.265 Compression Standard		Main Profile@Leve4.1 High Tier		
Resolution		6MP (3072 × 2048), 5MP (2880 × 1620), 4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480× 240, CIF		
Main Stream		60Hz: 6MP/5MP(1~20fps);4MP/3MP/1080P/720P(1~30fps); 50Hz: 6MP/5MP(1~20fps); 4MP/3MP/1080P/720P(1~25fps)		
Sub Stream		60Hz: 720P/D1/ CIF (1~30fps);50Hz: 720P/D1/ CIF (1~25fps)		
Third Stream		60Hz: D1/480× 240/CIF (1~30fps);50Hz: D1/480× 240/CIF(1~25fps)		
Bit Rate		64 Kbps ~ 8 Mbps		
Bit Rate Type		VBR / CBR		
Image Settings		ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser		
ROI		Each ROI to be configured separately		
Functions				
Remote Monitoring		Web browser /TVT NVR/NVMS2.X/Mobile APP		
Web Browser		IE (plug-in required)/Google Chrome/Edge/Firefox/Safari		
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission		
Network Protocol		UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, RTMP, HTTP, HTTPS, QoS		
Interface Protocol		ONVIF		
Storage		Network remote storage; micro SD card storage		
Smart Alarm		Motion detection, SD card full, SD card error		
Smart Event		Video Exception (scene change, video blur and video cast detection), line crossing detection, region intrusion detection, abandoned/missing object detection		
General Function		Watermark, IP address filtering, video mask, heartbeat, illegal login lock, corridor pattern		
PoE		Yes		
IR Distance		30 ~ 50 m		
Ingress Protection		IP67		
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	67.93m(222.86ft)	27.17m(89.14ft)	13.59m(44.58ft)	6.79m(22.27ft)
2.8~12mm(T)	183.75m(602.85ft)	73.50m(241.14ft)	36.75m(120.57ft)	18.37m(60.26ft)
Interfaces				
Network	RJ45			

Video Output	No
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in micro SD card slot, up to 256GB
Reset	Yes
Others	
Power Supply	DC12V/PoE
Power Consumption	< 8.5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F);Humidity: less than 95 % (non-condensing)
Storage Environment	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Ø 111.5 × 99.6
Weight (net)	Approx. 0.65KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9565S4(D/AZ/PE/AR3)	Motorized zoom lens
-----------------	------------------------	---------------------