

# Intercom Station

## TVT-MONITOR

Suitable to use with the TVT-INTERCOM



**Arrowhead**  
Alarm Products



### Features

- 7 inch touch screen
- Supports 2.4G WiFi
- "Do Not Disturb" function
- Noise suppression and echo cancellation
- 8 channel zone alarm access function
- Password lock
- A maximum of 6 indoor stations can be installed in the same room
- Live preview of door stations and linked cameras
- Snapshot when calling via door station (micro SD card required)
- 2 year return to base warranty





System	Operating System	Linux
Display	Display Screen	7 inch IPS touch screen
	Display Resolution	1024 × 600, brightness:300 cd/m2
	Operation Method	Capacitive touch screen
Video	Video Input	Max. 4CH videos can be viewed simultaneously
	Network Input Resolution	6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF
	Compression	H.265+/H.265/ H.264 / MJPEG
Audio	Local Input	Built-in microphone
	Local Output	Built-in speaker
	Compression	G.711(U/A)
Record	Resolution	Up to 2MP
	Frame Rate	NTSC: 30fps; PAL:25fps
Playback	Simultaneous Playback	Max.1CH
Performance	Linked IPC	Max. 16 CH
	Linked Indoor Extensions	Max. 5
Network	Interface	RJ 45 100 Mbps self-adaptive Ethernet port × 1
	Wireless Network	WiFi 802.11b/g/n
	Protocol	TCP / IP, DHCP, DNS, NTP, etc.
	Incoming/Outgoing Bandwidth	40/40Mbps
Interface	Audio	Built-in speaker and microphone, support noise suppression and echo cancellation
	Storage	Built-in micro SD card slot, up to 256GB
	Reset	Yes
	Alarm Input	8CH
	Wi-Fi	Yes,2.4G Wi-Fi
	Unlocking Button	Yes
	RS 485	Reserved
Others	Power Output	DC12V 200mA (only available when DC12V power supply is used)
	Power	DC12V/POE
	Power Consumption	< 6W
	Dimensions(mm)	180.6×135.6×26.8
	Weight (net)	Approx.0.36kg
	Installation	Wall mounting
	Working Environment	-20°C~50°C, Humidity: less than 95% (non-condensing)
	Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE	



### Dimensions

Unit (mm)

